

FABRIJET

HS FT III

1.9m HIGH SPEED FABRIJET TRANSFER

- Slots for various printheads arrangement
- Linear motor applied for high speed and high quality printing
- Up to 6 color channels (fluorescent and light colors)
- Mobile monitoring
- Limited coverage of 3 years' warranty



Print Speed (4 heads)	250m ² /hr (2,691ft ²)	150m ² /hr (1,615ft ²)	100m ² /hr (1,076ft ²)	75m ² /hr (807ft ²)
Print Resolution (4 heads)	600 x 300dpi 2Pass	600 x 600dpi 4Pass	600 x 900dpi 6Pass	600 x 1,200dpi 8Pass
Print Speed (3 heads)	210m ² /hr (2,260ft ²)	150m ² /hr (1,615ft ²)	115m ² /hr (1,238ft ²)	70m ² /hr (753ft ²)
Print Resolution (3 heads)	600 x 300dpi 1Pass	600 x 300dpi 2Pass	600 x 600dpi 2Pass	600 x 600dpi 4Pass
Max Print Width	1,850mm / 72.8 inch			
Max Media Load	1,900mm / 400mm / 250kg (74.8inch / 15.7inch / 550lb)			
Print Mode	Bi-Direction / Uni-Direction , Normal / Interleave			
Printhead	Kyocera - 3 / 4 ea (2 Channel)			
Color	4 Colors (K, C, M, Y) / 6 Colors (Fy, Fp / Lm, Lc)			
Ink	DGI original water based dye sublimation ink			
Interface	TCP / IP , USB 3.0			
Environmental Range	Temperature : 20~30°C (68~86°F) Humidity : 40~70% Environment condition may affect on final printing quality.			
Electricity Requirements	Single phase, 200-240V, 50/60 Hz, 42A (Printer: 10A, Dryer I: 16A, Dryer II: 16A)			
Applicatons	Clothes / Swimming Suit / Towels			

※ All specifications are subject to change without prior notice.

Dimension for Installation

	Uncrated				Crated			
	Length (mm)	Width (mm)	Height (mm)	무게 (kg)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
Printer	4,200	1,450	1,710	1,760	4,700	1,890	2,100	2,500
Winder	3,100	630	990	245	3,470	910	1,290	400

