

FD-1908

Specifications

Print head	Piezo type print heads						
Ink	DGI Original Reactive Ink						
Drop Size	5~18 Pico liter Variable dots						
Media	Cotton, Polyester, Silk and etc						
Max Print Width	1,850mm						
Max Media Width	1,900mm						
Print Mode	Bi / Uni Direction, Normal/ Interleave/ Purge						
Interface	TCP / IP, USB 3.0						
Resolution(DPI)	Max 600 DPI X1,800 DPI						
Rip Software	Wasatch TX, Inedit(Driver), Ergosoft(Driver)						
Color	8 Colors (Yellow, Magenta, Cyan, Black, Blue, Red, Orange, Gray)						
Operating environment	Temperature : 22~30℃ Humidity : 40~70%						
Electric Power	Printer : Single Phase, 220~240V, 50/60Hz, 11A						
	Dryer : 3-Phase, 380V, 50/60Hz, 40A						
Pressured Air	Min 5 kgf/cm ²						
Dimension	Printer - Uncrated : 4,410mm(L) x 1,820mm(W) x 1,630mm(H) Crated : 4,700mm(L) x 2,160mm(W) x 2,150mm(H)						
	Dryer - Uncrated : 3,720mm(L) x 1,160mm(W) x 1,256mm(H) Crated : 4,000mm(L) x 1,840mm(W) x 1,950mm(H)						
Weight	Printer - Uncrated : 1,630Kg Crated : 2,400 Kg						
	Dryer - Uncrated : 1,265Kg Crated : 1,700Kg						
Print Speed	Main Scan (DPI)	Mode	Sub Scan (DPI)	Speed (m ² /h)			Pass
				Normal	DBF I	DBFII	
	600	Normal	600	200	185	110	1
			1200	110	95	55	2
			1800	75	65	40	3
		Interleave I	600	125	112	68	2
			1200	67	60	34	4
			1800	45	40	23	6
		Interleave II	600	140	126	71	1
			1200	72	64	36	2
1800			65	58	24	3	